

10/583881
AP3 Rec'd PCT/PTO 21 JUN 2008

EV799415773US

DOCKET: CU-4891

IN THE UNITED STATES PATENT & TRADEMARK OFFICE

APPLICANT: Michio NISHI et al)
)
TITLE: METHOD OF RECOVERING A BASE PAPER FOR)
GYPSUM BOARD AND APPARATUS OF)
RECOVERING A BASE PAPER FOR GYPSUM)
BOARD)
)
COMPLETION OF PCT/JP2004/018148 filed December 6, 2004)

ENGLISH TRANSLATION OF PCT ARTICLE 34 AMENDMENTS

AP3 Rec'd PCT/PTO 21 JUN 2008
-7/1-

material of gypsum board, and washing the separated paper
piece with water using a rotary drum-type washing device
so as to eliminate a gypsum component adhering to the
paper piece, and further comprising a step of previously
5 dispersing or mixing the separated paper piece into a
portion of washing water before the separated paper piece
is introduced to the rotary drum-type washing device.

The apparatus of recovering a base paper for
gypsum board according to the present invention comprises
10 a device configured to break a waste material of gypsum
board, a device configured to separate a burnt gypsum
component and a paper piece from the broken waste material
of gypsum board, a rotary drum-type washing device
configured to wash the separated paper piece with water so
15 as to eliminate a burnt gypsum component adhering to the
paper piece, and a device configured to dewater the water-
washed paper piece, and further has a device configured to
disperse or mix the separated paper piece into water
before washing the separated paper piece with water.

20

ADVANTAGEOUS EFFECT OF THE INVENTION

According to the present invention, a method of
recovering a base paper for gypsum board and an apparatus
of recovering a base paper for gypsum board can be
25 provided which are capable of recovering a paper piece of
the base paper for gypsum board from a waste material of
gypsum board continuously and efficiently.

BRIEF DESCRIPTION OF THE DRAWINGS

30 FIG. 1 is a flowchart showing steps of
processing a waste material of gypsum board in an
embodiment of the present invention.

FIG. 2 is a schematic diagram showing the

-7/2-

configuration of an apparatus for processing a waste material of gypsum board in an embodiment of the present invention.

-25-

CLAIMS

1. (Amended) A method of recovering a base paper
for gypsum board, which is configured to recover a base
5 paper for gypsum board from a waste material of gypsum
board comprising a gypsum core and the base paper for
gypsum board adhering thereto, characterized by comprising
steps of

breaking the waste material of gypsum board,
10 separating a gypsum component and a paper piece
of the base paper for gypsum board from the broken waste
material of gypsum board, and

washing the separated paper piece with water
using a rotary drum-type washing device so as to eliminate
15 a gypsum component adhering to the paper piece, and
further comprising a step of

previously dispersing or mixing the separated
paper piece into a portion of washing water before the
separated paper piece is introduced to the rotary drum-
20 type washing device.

2. The method of recovering a base paper for
gypsum board as claimed in claim 1 characterized by
further comprising a step of burning the broken waste
25 material of gypsum board or the separated paper piece,
wherein the burning step is provided before the water
washing step.

3. The method of recovering a base paper for
30 gypsum board as claimed in claim 1 characterized by
further comprising a step of dewatering the water-washed
paper piece.

-26-

4. (Canceled)

5. The method of recovering a base paper for gypsum board as claimed in claim 1, wherein a ratio of a weight of the separated paper piece to a weight of fresh water in the washing water is in a range of 1 : 5 - 1 : 100.

6. The method of recovering a base paper for gypsum board as claimed in claim 5, wherein, in the step of previously dispersing or mixing the separated paper piece into a portion of washing water, a ratio of a weight of the separated paper piece to a weight of the portion of washing water is in a range of 1 : 1 - 1 : 15.

15

7. The method of recovering a base paper for gypsum board as claimed in claim 3, characterized in that the step of dewatering the paper piece comprises squeezing and dewatering of the water-washed paper piece.

20

8. (Amended) An apparatus of recovering a base paper for gypsum board, characterized by comprising a device configured to break a waste material of gypsum board,

25 a device configured to separate a burnt gypsum component and a paper piece from the broken waste material of gypsum board,

a rotary drum-type washing device configured to wash the separated paper piece with water so as to eliminate a burnt gypsum component adhering to the paper piece, and

30

a device configured to dewater the water-washed paper piece, and further having

-27-

a device configured to disperse or mix the separated paper piece into water before washing the separated paper piece with water.

5 9. The apparatus of recovering a base paper for gypsum board as claimed in claim 8, characterized by further comprising a device configured to burn the broken waste material of gypsum board.

10 10. (Canceled)

 11. The apparatus of recovering a base paper for gypsum board as claimed in claim 8, characterized in that the dewatering device is a device configured to squeeze
15 and dewater the water-washed paper piece.